

# How to Sync a Checkbox Custom Field in Jira Cloud

Last Modified on 04/15/2024 4:21 am EDT

This article shows how to synchronize a checkbox custom field.

Let's assume you have a checkbox named **Product Choices**.

## Source Side

### Outgoing sync

```
replica.customFields."Product Choices" = issue.customFields."Product Choices"
```

## Destination Side

Collect all values of the remote checkbox and find the corresponding value.

### Incoming sync

```
/*  
** Collect all values of the remote checkbox and find the corresponding value  
** Ignore in case the value is not found  
*/  
def checkboxCollection = replica.customFields."Product Choices".  
  value?.  
  collect{  
    a->  
      nodeHelper.getOption (issue, "Product Choices", a.value)  
  }  
issue.customFields."Product Choices".value = checkboxCollection
```

Check/uncheck depending of certain conditions.

### Incoming sync

```
if(replica.status.name == "Done"){  
  issue.customFields."Remote Status".value = ["Done"] //Check Done checkbox  
}else{  
  issue.customFields."Remote Status".value = [] //Uncheck all checkboxes  
}
```

Product

[About Us](#)

[Release History](#)

#### ON THIS PAGE

[Glossary](#)

[About Us](#)

[Security](#)

[Destination Side](#)

[Pricing and Licensing](#)

#### Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

Find a Partner

[YouTube Channel](#)

[Ebooks](#)

**Still need help?**

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)