

How to Sync Label Custom Fields in Jira Cloud

Last Modified on 04/10/2024 7:14 am EDT

This article shows how to synchronize a label custom field.

Let's assume you want to synchronize a label custom field named **label - cust1**.

Source Side

Outgoing sync

```
replica.customFields."label - cust1" = issue.customFields."label - cust1"
```

Destination Side

Incoming sync

- Set the received label to the local label custom field and if it doesn't find one, it sets an empty array so you don't get a null pointer exception

Note: This method overrides all the existing labels in the custom field.

```
issue.customFields."label - cust1".value = replica.customFields."label - cust1"?.value ?: []
```

- Add the received label into the local label custom field

```
issue.customFields."Labels".value += replica.customFields."label - cust1"?.value
```

How to set a Default Value in a Label Custom Field

To set a default value in a label custom field use the [nodeHelper](#).`getLabel` method.

```
issue.customFields."Epic/Theme".value = replica.customFields."Tags"?.value ?: [
    nodeHelper.getLabel("")
]
```

Product ON THIS PAGE

[About Us](#)

[Release History](#)

[Glossary](#)

[Destination Side](#)

[API Reference](#)

[How to set a Default Value in a Label Custom Field](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

Still need help?

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 