

How to Sync SecurityLevel Issue Field in Jira On-premise

Last Modified on 04/09/2024 8:27 am EDT

This article provides description and scripts that help to synchronize issue security level.

An issue security scheme is associated with a project, its security levels can be applied to issues in that project. You can synchronize the issue security level as any other issue field.

[SecurityLevel issue field](#) reference.

Source Instance

Add the issue security level to your **Outgoing sync** to send it to the Destination Instance:

```
replica.securityLevel = issue.securityLevel
```

Destination Instance

There are two methods to get securityLevel from the source side. The method depends if the securityLevel names are identicals on both sides.

- ***SecurityLevel names are identical on both sides***

Add the following code into the **Incoming sync** to add received security level field on the Destination side.

```
issue.securityLevel = replica.securityLevel
```

- ***SecurityLevel names don't match***

Add the code below into the **Incoming sync** to map different security levels between Instances.

```
import com.exalate.basic.domain.hubobject.v1. BasicHubIssueSecurityLevel
issue.securityLevel = new BasicHubIssueSecurityLevel(null, "name", "description")
```

Note: The [proxy user](#) needs to have permissions to access the security levels you are trying to set.

- Please check that the proxy user has access to all the security levels
- In the permission scheme - ensure that the proxy user has 'Set Issue Security' permission


ON THIS PAGE

[About Us](#)

[Release History](#)

[Release Notes](#) 

[Source Instance](#)

[Glossary](#) 

[Desktop Instance](#) 

[Security](#) 

[Pricing and Licensing](#) 

Resources

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

Still need help?

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 