

# Initiate a Private Connection in Basic Mode for ServiceNow

Last Modified on 03/12/2024 11:32 am EDT

## Note: For Private Connections:

- an instance you have access to is considered a public side.
- an instance you don't have access to is considered a private side: destination instance.

The main difference between private and public connection types is whether the HTTP/HTTPS requests are initiated from one side or from both sides. In this case, HTTP/HTTPS requests are initiated from the destination's private side only.

## Introduction


Connections in Basic mode have a set of **Sync Rules**, generated by Exalate. In Basic connections, you can only sync incidents. All comments are synced as public comments.

You cannot modify **Sync Rules** in Basic Mode.

If you want to edit/delete Sync Rules, you can upgrade the connection to Visual Mode or Script Mode.

## Initiate a Private Connection from ServiceNow

1. Navigate to the **Connections** tab in the Exalate console.



2. Click **Initiate Connection**.

**Connections**

Connection defines synchronization behavior, including communication details, sync rules, and scope.

**Initiate connection** **Accept invitation**

3. Click **'I don't have a URL'**

If the destination instance is in a private network click **I don't have a URL**. Exalate suggests available connection types based on the destination instance's version of Exalate.

**Initiate connection** x

Destination instance URL ⓘ

https://example.exalate.net

I don't have a URL

**Next**

4. Choose a **Basic** connection mode.

5. Click **Next**.

**Initiate connection** x

Destination instance URL ⓘ

https://example.exalate.net ✓

I don't have a URL

Choose the configuration type

**Basic**

- Automatic configuration of basic fields
- Sync rules cannot be edited
- Only issues can be synced
- Recommended for use cases of basic complexity

**Script**

- Groovy-based scripting
- Configure each side of the connection separately
- Recommended for use cases of basic to advanced complexity


**Next**

6. Click **Next**.

**Note:** As this is a Public-Private connection and you don't have admin access to the other side, you can continue to configure on your end and then send an invitation to your partner.

## 7. Click **Copy Invitation Code**

Here you can copy the invitation code and send it over to your partner. The destination side is shown as "unknown" since this is a private side.



## 8. Click **Done**

Once your partner accepts the invitation, you can start synchronization.

**Note:** When the connection is set up on the Public source side, the Private side administrator should accept the invitation in the Private-Public connection.

To do so, click on the **Accept invitation** button in the **Connections** tab of the Exalate Admin Console and paste the copied invitation code.

Product  
About Us  
Release History

Glossary

API Reference

Security

Pricing and Licensing

### Resources

Academy

Blog

YouTube Channel

Ebooks

### Still need help?

Join our Community

Visit our Service Desk

Find a Partner