

How to Sync Statuses in Azure DevOps

Last Modified on 08/06/2024 10:32 am EDT

In this article, we describe how to sync status between instances.

You need to configure the mapping between statuses on both sides. The example below works for all supported issue tracking platforms.

Source Side

Outgoing sync

Send local status to the remote side:

```
replica.status = workItem.status
```

Incoming sync

Set the local status based on the received status value from the remote side:

```
def statusMap = [  
  
  // "remote status name": "local status name"  
  "To Do" : "New",  
  "In Progress" : "Working on it",  
  "Done" : "Canceled"  
]  
  
def remoteStatusName = replica.status.name  
workItem.setStatus(statusMap[remoteStatusName] ?: remoteStatusName)
```

Alternatively, you can set the default local status using the [getStatus](#) node helper method.

Product

```
workItem.setStatus("status name")
```

[About Us](#)

[Release History](#)

[Glossary](#)

[API Reference](#)

Have more questions? [Ask the community](#)

[Security](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)