How to Sync Area and Iteration Paths in Azure DevOps Server & Service

Last Modified on 10/26/2025 8:30 pm EDT

This article shows how to synchronize Area and Iteration Paths in Azure DevOps.

Source Side(Azure DevOps)

Outgoing sync

To send out the area and iteration paths from Azure DevOps work item use the code below:

replica.areaPath = workItem.areaPath replica.iterationPath = workItem.iterationPath

You can store the area/iteration path on the remote side in a custom field of type string or the select list.

Destination Side (Azure DevOps)

Incoming sync

- · Area Path field
- · Iteration Path field

Area Path Field

You can set the Area Path based on a string value received from the remote side.

It always starts with the name of the project, for example, *AzureNode* project and *Exalate*, as the area may have the Area Path *AzureNode*||*Exalate*.

If you don't set the value for the Area field in the Sync Rules, Exalate uses the default area that has the same name as the project.

To set the AreaPath manually use the code below:

workItem.areaPath = "Name of the project\\name of the area"

To set the Area Path based on the value received from the remote side drop-down list, use the code below:

workltem.areaPath = replica.customFields."area-path-select-list"?.value?.value // change "area-path-select-list" to the relevant custom field name

To set the Area Path based on the value received from the remote side text field, use the code

work Item. area Path = replica. custom Fields. "area-path". value

Iteration Path Field

You can set the Iteration Path based on a string value received from the remote side.

It always starts with the name of the project, for example, *AzureNode* project and *Sprint 1*, as the iteration may have the Iteration Path *AzureNode//Sprint 1*.

If you don't set the value for the Area field in the Sync Rules, Exalate uses the default area that has the same name as the project.

To set the Iteration Path manually use the code below:

workItem.iterationPath = "Name of the project\\name of the iteration"

To set the Iteration Path based on the value received from the remote side drop-down list, use the code below:

workItem.iterationPath = replica.customFields."iteration-path-select-list"?.value?.value // change "iteration-path-select-list" to the relevant custom field name

To set the Iteration Path based on the value received from the remote side text field, use the code below:

Product

workItem.iterationPath = replica.customFields."iteration-path".value

Glossary ?

Have more questions? Ask the community

Security ?

Pricing and Licensing ?

Resources

Subscribe for a weekly Exalate hack 2

Academy ?

Blog ?

YouTube Channel ?

Fhooks ?

Still need help?

Join our Community 3

Visit our Service Desk ?

Find a Partner ?