

getLocalIssueKeyFromRemoteld

Last Modified on 05/15/2024 5:51 am EDT

Signature

| | |
|---------------|---|
| Helper | nodeHelper |
| Signature | getLocalIssueKeyFromRemoteld (Long remotelssued) |
| Description | Finds a local issue key linked to a remote issue. |
| Introduced in | 2.4.0 |

Parameters

| | |
|--------------|---|
| remotelssued | The ID of the issue of the remote side. |
|--------------|---|

Example use

You can use this method to synchronize sub-tasks from Jira to Azure DevOps, or between Azure DevOps instances.

Outgoing sync (sending side)

```
replica.parentId = issue.parentId
```

Incoming sync(receiving side)

```
if(replica.parentId){  
    def localParent = syncHelper.getLocalIssueKeyFromRemoteld(replica.parentId.toLong())  
    if(localParent){  
        issue.parentId = localParent.id  
    }  
}
```

For Jira On-Premise

Outgoing sync (sending side)

```
replica.parentId = issue.parentId
```

Incoming sync(receiving side)

```
if(replica.parentId){  
  
    def localParent = synchelper.getLocalIssueKeyFromRemoteId(replica.parentId.toLong(),"issue")  
  
    if(localParent){  
        issue.parentId = localParent.id  
    }  
}
```

Note: Both the parent task and the sub-task must be in sync for the parent link to be created in the child issue.

Product

[About Us](#)

[Release History](#)

[Glossary](#)

Comments

- If no local issue is linked to the provided remote issue ID, the method will return null.

[Security](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)