

getOptions

Last Modified on 04/15/2024 6:44 am EDT

Signature

Helper	nodeHelper
Signature	<ul style="list-style-type: none"><code>getOptions(Issue issue, String customFieldName, List of Strings names)</code><code>getOptions(Issue issue, Long customFieldId, List of Strings names)</code>
Description	Allows retrieving a list of options from a custom field.
Introduced in	0.8

Example use

Set options **Happy**, **Sad**, **Lucky** to the custom field **Mood**.

```
def moodOptions = nodeHelper.getOptions(issue, "Mood", ["Happy", "Sad", "Lucky"])
issue.customFields."Mood".value = moodOptions
```

Using the Custom Field Id instead of the Custom Field Name

Set received options to the local custom field with ID 10201.

```
// When using field's id, add L at the end of the Id. E.g. 10201L is custom field id with L added at the end.
issue.customFields."10201".value = nodeHelper.getOptions(issue, 10201L, replica.customFields."Remote select List C
F Id".value.collect {it -> it.value})
```

Comments

- [Product](#)
[Announcements](#)
[Release History](#)
[Glossary](#)
[API Reference](#)
[Security](#)
- The options are only available for custom fields with distinct values such as a select, radio button, or checkbox custom field.

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)

