

# getOption

Last Modified on 04/15/2024 6:46 am EDT

## Signature

Helper	nodeHelper
Signature	<code>getOption(Issue issue, String customFieldName, String optionName)</code> <code>getOption(Issue issue, Long customFieldId, String optionName)</code>
Description	Allows retrieving an option from a single select list custom field with the help of a custom field name or ID.
Introduced in	0.8

## Example use

```
def moodOption = nodeHelper.getOption(issue, "Mood", replica.customKeys.mood)
issue.customFields."Mood".value = moodOption
```

## Using the Custom Field Id instead of the Custom Field Name

Set the received value from the remote select list custom field to the local custom field with ID 10201.

```
// When you use field id add L at the end of the Id. E.g. 10201L is custom field id with L added at the end.
issue.customFields."10201".value = nodeHelper.getOption(issue, 10201L, replica.customFields."Remote Select List CF
Id".value.value)
```

## Comments

- Options are available only for custom fields with values such as a select list, radio button or checkbox.

When you use `.value` in a script, you'll get all option-related data.

```
issue.customFields."Mood".value==`[[id:10, value:Happy], [id:11, value:Sneezy]]`
```

Product

When you use `.value.value` you'll get only the option value without additional data.

[About Us](#)

[Release History](#)

```
issue.customFields."Mood".value.value==`[Happy, Sneezy]`
```

[API Reference](#)

[Security](#)


[Pricing and Licensing](#) 

**Resources**

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

**Still need help?**

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 