

getUser

Last Modified on 04/15/2024 6:05 am EDT

Note: For the method to work on Azure DevOps, make sure that the user is part of the team that has access to the Azure DevOps project.

Signature

Helper	nodeHelper
Signature	<p>Jira Server: <code>getUser(String userKey)</code></p> <p>Jira Cloud: <code>getUser(String accountId)</code></p> <p>Azure DevOps:</p> <p><code>getUser(String userKey), getUserByUsername(username: String)</code> is the same as <code>getUserByFullName(username: String)</code></p> <p>Salesforce: <code>getUser(String userKey)</code></p>
Description	Returns a user object Null in case the user is not found
Introduced in	0.8

Note: The Signature introduced in 0.8 works for Azure Devops until version 5.4.0.

Example use

Product
Set the local issue assignee based on the remote issue assignee using the method.

[Release History](#)

[Glossary](#)

[issueAssignee = NodeHelper.getUser\(replica.assignee.key\)](#)

[Security](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)