

# getCustomFieldDefaultValue

Last Modified on 04/15/2024 6:55 am EDT

h2 id="getCustomFieldDefaultValue-Signature">Signature

Helper	nodeHelper
Signature	<p>There are multiple signature options:</p> <ul style="list-style-type: none"><li>• <code>getCustomFieldDefaultValue(String name, IHubIssueType type, IHubProject project)</code></li><li>• <code>getCustomFieldDefaultValue(Long id, IHubIssueType type, IHubProject project)</code></li><li>• <code>getCustomFieldDefaultValue(String name, IHubIssue issue)</code></li><li>• <code>getCustomFieldDefaultValue(Long id, IHubIssue issue)</code></li></ul>
Description	Returns the default value of the <a href="#">customfield</a>
Introduced in	0.9.1

## Example use

```
issue.project = nodeHelper.getProject("Staff")
issue.issueType = nodeHelper.getIssueType("Hobby")

if (replica.customKey.mood == null) {
  issue.customFields.mood.value = nodeHelper.getCustomFieldDefaultValue("mood", issue.issueType, issue.project)
}
```

[API Reference](#)

[Security](#)

[Pricing and Licensing](#)

### Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

### Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)