

How to Install Exalate for Zendesk on Docker

Last Modified on 03/26/2025 6:02 pm EDT

You can host Exalate for Zendesk on your own server. To do so, you need to install Exalate on Docker.

Note: You need to install Docker. Check the [docker documentation](#) for more details.

How to Install Exalate for Zendesk on Docker

1. Create directory and create docker-compose.yml file

Create a directory to hold the docker-compose file:

```
cd ~  
mkdir exalate-zendesknode
```

Create or download a **docker-compose.yml** file

Note: Click [docker-compose.yml](#) to download the file.

Important: We recommend using the latest version of Exalate for Zendesk. It can be found in the [Release History](#). Enter the latest version in the `image` tag. For example, in `image: idalko/zendesknode:5.23.0`, the version of Exalate for Zendesk is `5.23.0`.

The **docker-compose.yml** file should contain the following information in it:

```
services:
  database:
    restart: unless-stopped
    image: postgres:12.19
    volumes:
      - ./persist/db:/var/lib/postgresql/data
      - ./createdb.sh:/docker-entrypoint-initdb.d/init-user-db.sh
    environment:
      - POSTGRES_PASSWORD=changeme
      - DB_NAME=zendesknode
      - DB_USER=exalate
      - DB_PASS=exalate
    networks:
      - dbnet

  zendesknode:
    restart: unless-stopped
    ports:
      - 9302:9002

    #
    # Change the image tag to the required version
    # Check Release History on docs.exalate.com for an overview
    #
    image: idalko/zendesknode:5.23.0
    depends_on:
      - database #wait for postgres to be started, not for ready
    volumes:
      - ./persist/home:/opt/zendesknode/data
    environment:
      # Add your environment settings here
      - ZENDESKNODE_PG_HOST=database
      - ZENDESKNODE_PG_DB=zendesknode?gssEncMode=disable
      - ZENDESKNODE_PG_USER=exalate
      - ZENDESKNODE_PG_PWD=exalate
      - ZENDESKNODE_PORT=9302

    #As part of the security improvements, Exalate 5.5.0 and above validates the origin header
    #that the browser is sending upon every request to Exalate.
    #In order to validate the origin header, Exalate needs to know what is the URL
    #leading to it.
    #When deploying Exalate to Docker one needs to put an environment variable NODE_SELF_URL
    .
    #Example:
    # When you deploy Exalate onto a server, you configure a DNS rule such that
    #whenever people navigate to foo.com, they reach your server's Exalate.
    #You set up SSL so that https://foo.com leads to your Exalate on your server.
    #Now you need to set environment variable

    - NODE_SELF_URL=https://foo.com

    #for your Exalate docker container.

    networks:
      - dbnet
      - default

networks:
  dbnet:
    driver: bridge
  default:
    driver: bridge
```

Note: the - **SALESFORCENODE_PG_DB=** and - **DB_NAME=** must match in order to start the db correctly.

Connecting to Postgres 10 or Higher

For unencrypted connections from Exalate to a Postgres version 10 or higher, you need to disable `gssEncMode` with the following setting:

```
# exalate is the name of the database on the postgres instance
#
ZENDESKNODE_PG_DB=exalate?gssEncMode=disable
```

2. Ensure that a correct database is setup using a createdb.sh

Create or download a **createdb.sh** file (referenced from docker-compose.yml):



Note: Click [createdb.sh](#) to download the file.

The file **must be executable** and should contain the following information:

```
#!/bin/bash

TEST=`psql -U postgres <<-EOSQL
SELECT 1 FROM pg_database WHERE datname='${DB_NAME}';
EOSQL`

echo "*****CREATING DOCKER DATABASE*****"
if [[ $TEST == "1" ]]; then
  # database exists
  # $? is 0
  exit 0
else
  psql -U postgres <<-EOSQL
  CREATE ROLE $DB_USER WITH LOGIN ENCRYPTED PASSWORD '${DB_PASS}' SUPERUSER;
  EOSQL

  psql -U postgres <<-EOSQL
  CREATE DATABASE $DB_NAME WITH OWNER $DB_USER ENCODING 'UNICODE' LC_COLLATE 'C' LC_CTYPE 'C' TEMPLATE template0
  ;
  EOSQL

  psql -U postgres <<-EOSQL
  GRANT ALL PRIVILEGES ON DATABASE $DB_NAME TO $DB_USER;
  EOSQL
fi

echo ""
echo "*****DOCKER DATABASE CREATED*****"
```

Ensure that the volumes are included in your backup strategy:

- persist

3. Set Environment Variables if necessary

Below, you can find the environment variables used for the app container. All of them are optional, and in the given example, we've overridden ZENDESKNODE_PG_DB, ZENDESKNODE_PG_USER, and ZENDESKNODE_PG_PWD just to show how to pass different credentials to the Exalate application.

Full list of environment variables:

Variable name	Default value	Example	Descrip
HTTP_HEADER	n/a	HTTP_HEADERS="TestName1: testAddHeader1"	Allows a between through
ZENDESKNODE_PG_HOST	ZENDESKNODE_PG_HOST=database	ZENDESKNODE_PG_HOST=db.acme.com	Tells the the Post is hosted
ZENDESKNODE_PG_DB	ZENDESKNODE_PG_DB=exalate	ZENDESKNODE_PG_DB=exalate	Tells the the Post Exalate
ZENDESKNODE_PG_USER	ZENDESKNODE_PG_USER=idalko	ZENDESKNODE_PG_USER=exalate	Tells the the Post the Exal queries
ZENDESKNODE_PG_PWD	ZENDESKNODE_PG_PWD=idalko	ZENDESKNODE_PG_PWD=secret	Tells the the Post password to perform

Variable name	Default value	Example	Description
ZENDESKNODE_PORT	ZENDESKNODE_PORT=9000	ZENDESKNODE_PORT=8080	Tells which port the application listens on. <i>Note that the exalate node contains a default value of 9000, but this should be changed to 8080.</i> port: - 9000 should be port: - 8080
ZENDESKNODE_SMTP_HOST_NAME	ZENDESKNODE_SMTP_HOST_NAME=mail.server.com	ZENDESKNODE_SMTP_HOST_NAME=smtp.gmail.com	is used for outgoing email about error reports and synchronization
ZENDESKNODE_SMTP_PORT	ZENDESKNODE_SMTP_PORT=465	ZENDESKNODE_SMTP_PORT=587	is used for outgoing email about error reports and synchronization
ZENDESKNODE_SMTP_FROM	ZENDESKNODE_SMTP_FROM=admin@admin.com	ZENDESKNODE_SMTP_FROM=my.name@gmail.com	is used for outgoing email about error reports and synchronization
ZENDESKNODE_SMTP_USER	ZENDESKNODE_SMTP_USER=admin	ZENDESKNODE_SMTP_USER=my.name	is used for outgoing email about error reports and synchronization
ZENDESKNODE_SMTP_PASS	ZENDESKNODE_SMTP_PASS=1234567	ZENDESKNODE_SMTP_PASS=secret	is used for outgoing email about error reports and synchronization
ZENDESKNODE_SMTP_TLS	ZENDESKNODE_SMTP_TLS=true	ZENDESKNODE_SMTP_TLS=true	is used for outgoing email about error reports and synchronization but there should be a note that ZENDESKNODE_SMTP_PASS should be set to a secure value and SSL and TLS should be enabled
FEATURE_AI_ASSIST_ENABLED	n/a	FEATURE_AI_ASSIST_ENABLED=true	Switches Exalate AI Assist. Enabled generates AI-generated responses. <i>*The AI Assist is a real-time feature.</i>

Using a Proxy for Outgoing Connections

Whenever the Exalate node needs to use a proxy to establish outgoing connections, use the following parameters in the environment (naming should be obvious):

- PROXY_HTTP_HOST
- PROXY_HTTP_PORT


- PROXY_HTTPS_HOST
- PROXY_HTTPS_PORT

4. Start the Application

```
cd ~/exalate-zendesknode
docker-compose up -d
```

Verify the installation

After performing the aforementioned steps and checking that the container is up, you should be able to access the Exalate console via <http://localhost:9302>



Note: You may need to set up [local port forwarding](#) in order to get this to work.

5. Register the Node

To be able to fully use the functionality of your new node, it needs to be registered on the mapper. This mapper acts as a DNS server, mapping tracker URLs to node URLs.

Please raise a [ticket on the support portal](#) providing the following:

- URL of the Zendesk instance.
- URL of the Exalate node which has been deployed on-premise.

How to Manage the Application on Docker

Run Queries to the Application's Database

```
cd ~/exalate-zendesknode
docker exec -it exalate-zendesknode_database_1 bash
su postgres
psql -A $DB_NAME
```

You can find all tables using PSQLs `\dt+` command:

```
\dt+
```

All the Postgres SQL queries are permitted

To exit the application's DB:

```
\q
# \q exits the psql
exit
# exits the postgres user session
exit
# exits the exalate-zendesknode_database_1 bash session
```

Inspect the Application's Filesystem

```
cd ~/exalate-zendesknode
docker exec -it exalate-zendesknode_zendesknode_1 bash
```

Remove the application

```
cd ~/exalate-zendesknode
docker-compose rm
```

Remove the application data

Warning: do this only if you want to delete all the synchronization information, including the current synchronizations enqueued to be performed, and synchronization status. Ensure that the remote side you exalate issues with knows that you're stopping synchronization and is ready to handle synchronization errors.

```
cd ~/exalate-zendesknode
# docker volume ls | grep exalate-zendesknode_vol | awk '{ print $2 }' | xargs docker volume r
m
docker volume rm exalate-zendesknode_voldatabase
docker volume rm exalate-zendesknode_volzendesknode
```

System Administration Tasks

With the Exalate for Jira Cloud is running on your environment, you are be required to do the mandatory system administration tasks

- Backup (& restore tests)
- Disaster recovery procedure
- Upgrades whenever needed

Note: Please note that an Exalate version has a lifespan of 2 years. This is to ensure backward compatibility over the whole platform. There are regular new versions deployed which contain bug fixes, security-related improvements, and even new features. Watch the [release notes](#) page for any new versions.

Upgrading Exalate on Docker

If you need to upgrade Exalate on Docker, here are the steps to follow:

1. Edit the YAML File :

Open the `docker-compose.yml` file in a text editor and modify the image tag for the service you wish to upgrade.

```
# use the latest version https://hub.docker.com/r/idalko/zendesknode
image: idalko/zendesknode:latest
depends_on:
  - database #wait for postgres to be started, not for ready
```

Replace `latest` with the latest or desired version tag.

2. Pull the Latest Image :

From the directory containing your `docker-compose.yml` file, pull the latest image.

```
docker-compose pull
```

3. Recreate the Container:

Using Docker Compose, you can easily recreate the container with the new image.

```
docker-compose up -d
```

The `-d` flag runs the containers in detached mode. Docker Compose automatically stops the old container and starts a new one based on the updated image.

4. Post-Upgrade Checks :

After starting the upgraded container, check to make sure everything is running as expected:

- Log into the Exalate interface and verify that all your configurations, connections are intact.
- Test out a few synchronizations to make sure they work as expected.
- Check for any errors in the Docker logs or the Exalate logs.

Troubleshooting

Issues during the installation of the Exalate server for Zendesk

If you have issues during the installation of the Exalate app for Zendesk, you can find logs describing possible problems inside `/tmp`.

The name for the file is generated randomly and automatically by the OS, but you can find the file by the creation date.

Issues while running the Exalate server for Zendesk

Logs are generated under the directory: `/opt/zendesknode/data/logs` .

Refer to these logs to get more information about possible issues and communicate with our support if you need any assistance.

Support

About Us [↗](#)

Please read our Support options.

Glossary [↗](#)

API Reference [↗](#)

ON THIS PAGE

Pricing and Licensing [↗](#)

Resources

Subscribe for a weekly Exalate hack [↗](#)

Academy [↗](#)

Blog [↗](#)

YouTube Channel [↗](#)

Ebooks [↗](#)

Still need help?

Join our Community [↗](#)

Visit our Service Desk [↗](#)

Find a Partner [↗](#)