

# How to Sync Status in Exalate for Freshservice

Last Modified on 06/18/2025 11:15 am EDT

To configure mapping to sync statuses in Freshservice, use the following rules:

## From Freshservice to Jira

### Freshservice Outgoing Sync Rules:

```
replica.status = entity.status
```

### Jira Incoming Sync Rules:

```
// Map Freshservice status ids to Jira status names
def statusMap = [
  "Open" : "Open",
  "Pending" : "Pending",
  "Work in progress" : "Resolved",
  "Done" : "Closed"
]
entity.status = nodeHelper.getStatus(statusMapping[replica.status?.name] ?: "Open")
```

In case the Freshservice ticket status is not provided in the map, the status in Jira will default to the fallback value specified (e.g., "Open" in the code example above).

## From Jira to Freshservice

### Jira Outgoing Sync Rules:

```
replica.status = issue.status
```

### Freshservice Incoming Sync Rules:

```
// Map Jira status names to Freshservice status names
def statusMap = [
  "Backlog" : "Open",
  "In progress" : "Open",
  "Done" : "Resolved"
]
entity.status = nodeHelper.getStatus(statusMapping[replica.status?.name] ?: "Open")
```

[Release History](#)

[Glossary](#)

In case the Jira issue status is not provided in the map, the status in Freshservice will default to the fallback value specified (e.g., "Open" in the code example above).

[API Reference](#)

[Security](#)

[Pricing and Licensing](#)

**Resources**

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

**Still need help?**

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)