How to Sync Parent-Child Tasks in Asana

Last Modified on 10/03/2025 1:47 pm EDT

How to Sync Parent-Child Tasks in Asana

This article describes how to synchronize parent-child task relationships (subtasks) between Asana and other systems.

Parent-Child Tasks: Asana supports subtasks linked to parent tasks. The parent task GID is stored in the parent task gid custom field.

Outgoing sync (Asana → Remote system)

To send parent-child relationship information from Asana:

```
replica.customFields.parent task gid = entity.customFields.parent task gid
```

Incoming sync (Remote system → Asana)

To receive parent-child relationship and establish hierarchy in Asana:

```
if(replica.parentId){
  \label{eq:def_local_parent} def_local_{Parent} = syncHelper.getLocal_{IssueKeyFromRemoteld}(replica.parentId.toLong(), "issue")
  if(localParent){
     issue.parentId = localParent.id
  } else {
     throw new com.exalate.api.exception.IssueTrackerException(
        "Subtask cannot be created: parent issue with remote id " +
        replica.parentId + " was not found"
  }
}
```

Important: Parent tasks must be synchronized before child tasks. If a child task syncs before its parent exists, the synchronization will fail with an error.

More information

- How to Sync Tasks in Asana
- How to Sync Custom Fields in Asana
- RAlsana เห็นอใต้s and Entities Available for Synchronization

Have More questions? Ask the community

```
Security ?
```

```
Pricing and Licensing ?
Resources
Subscribe for a weekly Exalate hack 2
Academy ?
Blog ?
```

YouTube Channel ?

Ebooks ?

Still need help?

Join our Community ?

Visit our Service Desk ?

Find a Partner 2