

How to Sync Tasks and Subtasks in Jira Cloud

Last Modified on 01/28/2026 6:49 am EST

With Exalate, you can sync tasks and subtasks while keeping the parent-child relationship on the remote side. See the example below.

Note: The example below works only for connections in Scripting mode. If you already created a connection in [Visual mode](#), you need to create a new connection in Scripting mode.

Source Side

Outgoing sync

Send the ID of the parent issue.

```
replica.parentId = issue.parentId
```

Destination Side

Incoming sync

Find the local parent issue with the help of the ***parent.Id received from*** the remote side.

To sync the parent link with a subtask, you need to first sync a parent task, and then only the related subtasks. So if you sync subtasks *before* the parent task, you will get an error.

```
if(firstSync && replica.parentId){
    issue.typeName = "Sub-task" //Make sure to use the right subtask type here.
    def localParent = nodeHelper.getLocalIssueFromRemoteld(replica.parentId.toLong())
    if(localParent){
        issue.parentId = localParent.id
    } else {
        throw new com.exalate.api.exception.IssueTrackerException("Subtask cannot be created: parent issue with remote id " + replica.parentId + " was not found. Please make sure the parent issue is synchronized before resolving this error")
    }
}
```

Syncing Subtasks Automatically after Syncing Parent Task (Jira Cloud)

Outgoing sync

```
// Automatically sync all subtasks when syncing parent task
httpClient.get("/rest/api/3/issue/" + issueKey.id).fields.subtasks?.collect{
    def subTaskKey = new com.exalate.basic.domain.BasicIssueKey(it.id, it.key)
    syncHelper.exalate(subTaskKey)
}
```

Syncing Subtasks in Visual Mode for Jira Cloud and Jira on-premise

With this script, you can specify how the subtask will be linked to the parent task.

```
if(firstSync && replica.parentId){  
    issue.typeName = "Sub-task" //Make sure to use the right subtask type here.  
    def localParent = nodeHelper.getLocallIssueFromRemotId(replica.parentId.toLong())  
    if(localParent){  
        issue.parentId = localParent.id  
    } else {  
        throw new com.exalate.api.exception.IssueTrackerException("Subtask cannot be created: parent issue with remote id " + replica.parentId + " was not found. Please make sure the parent issue is synchronized before resolving this error")  
    }  
}
```

ON THIS PAGE

[Source Side](#)

[Destination Side](#)

[Product](#)

[About Us](#) [Syncing Subtasks Automatically after Syncing Parent](#)

[Release History](#) [Task \(Jira Cloud\)](#)

[Glossary](#) [?](#)

[Syncing Subtasks in Visual Mode for Jira Cloud and Jira](#)

[API Reference](#) [?](#)

[on-premise](#) [?](#)

[Security](#) [?](#)

[Pricing and Licensing](#) [?](#)

[Resources](#)

[Subscribe for a weekly Exalate hack](#) [?](#)

[Academy](#) [?](#)

[Blog](#) [?](#)

[YouTube Channel](#) [?](#)

[Ebooks](#) [?](#)

Still need help?

[Join our Community](#) [?](#)

[Visit our Service Desk](#) [?](#)

[Find a Partner](#) [?](#)