

How to Sync Time Tracking Fields in Jira On-premise

Last Modified on 01/15/2026 6:27 pm EST

To synchronize time tracking fields such as **Original estimate**, **Remaining estimate** or **Time spent** you need to add following scripts into the corresponding synchronization processors. Setting the time spent in Jira Cloud directly is not supported, it needs to be set through [worklogs](#).

Source Instance

Outgoing sync

Send *Time tracking* information to the Destination Instance.

```
// Add the time tracking information to the datafilter
replica.timeSpent = issue.timeSpent
replica.originalEstimate = issue.originalEstimate
replica.remainingEstimate = issue.remainingEstimate
```

Destination Instance

Incoming sync

Apply received *Time tracking* information from the Source Instance.

```
// this will overwrite the current time tracking information

issue.timeSpent = replica.timeSpent
issue.originalEstimate = replica.originalEstimate
issue.remainingEstimate = replica.remainingEstimate
```

Product

[About Us](#) 

[ON THIS PAGE](#)

[Release History](#) 

[Glossary](#) 

[Source Instance](#)

[API Reference](#) 

[Destination Instance](#)

[Security](#) 

[Pricing and Licensing](#) 

Resources

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

Still need help?

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 