

getOption

Last Modified on 01/30/2026 11:10 am EST

Signature

Helper	nodeHelper
Signature	<code>getOption(Issue issue, String customFieldName, String optionName)</code> <code>getOption(Issue issue, Long customFieldId, String optionName)</code>
Description	Allows retrieving an option from a single select list custom field with the help of a custom field name or ID.
Introduced in	0.8

Example use

```
def moodOption = nodeHelper.getOption(issue, "Mood", replica.customKeys.mood)
issue.customFields."Mood".value = moodOption
```

Using the Custom Field Id instead of the Custom Field Name

Set the received value from the remote select list custom field to the local custom field with ID 10201.

```
// When you use field id add L at the end of the Id. E.g. 10201L is custom field id with L added at the end.
issue.customFields."10201".value = nodeHelper.getOption(issue, 10201L, replica.customFields."Remote Select List CF Id".value.value)
```

Comments

- Options are available only for custom fields with values such as a select list, radio button or checkbox.

When you use `.value` in a script, you'll get all option-related data.

```
issue.customFields."Mood".value==`[[id:10, value:Happy], [id:11, value:Sneezy]]`
```

Product

When you use `.value.value` you'll get only the option value without additional data.

About Us

Release History

```
issue.customFields."Mood".value.value==`[Happy, Sneezy]`
```

API Reference

Security

[Pricing and Licensing](#) ?

Resources

[Subscribe for a weekly Exalate hack](#) ?

[Academy](#) ?

[Blog](#) ?

[YouTube Channel](#) ?

[Ebooks](#) ?

Still need help?

[Join our Community](#) ?

[Visit our Service Desk](#) ?

[Find a Partner](#) ?