

# Adding basic external script in Jira

Last Modified on 02/17/2026 1:16 pm EST

This article shows an example of how you can create an example groovy file, add a script, and call it in the Sync Rules.

1. Make sure you have the **scripts** directory. The directory location depends on the issue tracking platform. Custom scripts can only be deployed on Jira Server/Datacenter and nodes which are deployed through the docker deployment approach.

Platform	location
Docker based	<pre>/opt/&lt;nodename&gt;/data/scripts</pre> <p>There could be one of the following values instead of <code>&lt;nodename&gt;</code> :</p> <ul style="list-style-type: none"><li>◦ <code>snownode</code> for Exalate for ServiceNow.</li><li>◦ <code>adnode</code> for Exalate for Azure DevOps</li></ul>
Jira Cloud	<p>Jira Cloud, just as any other cloud node, supports a set of specific scripts. Custom scripts cannot be deployed in this environment.</p> <p>Check out <a href="#">List of external scripts for Jira Cloud</a> for more information.</p>

2. Create **BasicFieldSync.groovy** file with the following code, and store it in the right location on your server. There is no need to restart instance/add-on to enable the external script.

```
class BasicFieldSync
{
    static receive(issue,
        replica,
        nodeHelper,
        commentHelper,
        attachmentHelper) {

        issue.summary    = replica.summary
        issue.description = replica.description
        issue.assignee   = nodeHelper.getUserByUsername(replica.assignee?.username)
        issue.reporter   = nodeHelper.getUserByUsername(replica.reporter?.username)
        issue.labels     = replica.labels
        issue.comments   = commentHelper.mergeComments(issue, replica)
        issue.attachments = attachmentHelper.mergeAttachments(issue, replica)
    }
}
```

3. Call the **BasicFieldSync.groovy** script from the Sync Rules.

- Replace the script in the outgoing sync rules (create and change processors) as below:

## Existing script

```
issue.summary = replica.summary
issue.description = replica.description
issue.assignee = nodeHelper.getUserByUsername(replica.assignee?.username)
issue.reporter = nodeHelper.getUserByUsername(replica.reporter?.username)
issue.labels = replica.labels
issue.comments = commentHelper.mergeComments(issue, replica)
issue.attachments = attachmentHelper.mergeAttachments(issue, replica)
```

## New script

```
BasicFieldSync.receive(
  issue,
  replica,
  nodeHelper,
  commentHelper,
  attachmentHelper
)
```

### Product

Now you have one file with basic synchronization rules. You can reuse it in outgoing sync processors, new issues(create processor) and for existing issues(change processor). If you add new code into the **BasicFieldSync.groovy**, it is automatically executed in your incoming sync rules (create and change processors).

[About Us](#)

[Release Notes](#)

[Code in](#)

[API Reference](#)

[Security](#)

[Pricing and Licensing](#)

[Resources](#)

**Resources**

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

**Still need help?**

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)