

Set up how often Exalate sends emails

Last Modified on 01/30/2026 12:44 pm EST

This article shows how to set the time period between Exalate emails. Exalate sends emails with [error notifications](#) to administrators. Use the `mail.smtp_backoff` variable to control how often you receive emails from Exalate. For example, you can set up Exalate to send an e-mail every 10 minutes.

1. Open the **setenv.sh** file in your Jira folder.

In the file, you can set properties and options on startup.

Note: For more information about adding variables in Linux and Windows, please check this [Atlassian article](#).

2. Locate the `JVM_SUPPORT_RECOMMENDED_ARGS=""` property and modify it to the following:

```
JVM_SUPPORT_RECOMMENDED_ARGS="-Dmail.smtp.backoff=10"
```

Product

[About Us](#) The `-Dmail.smtp.backoff` property is in minutes and it must be a positive number. For example, [Released History](#) If `Dmail.smtp.backoff=10`, Exalate will send an email every 10 minutes.

[Glossary](#) 

[API Reference](#) 

3. Restart the service.

[Security](#) 

[Pricing and Licensing](#) 

Resources

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

Still need help?

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 