

How to Sync Label Custom Fields in Jira On-premise

Last Modified on 02/11/2026 9:29 am EST

This article shows how to synchronize a label custom field.

Let's assume you want to synchronize a label custom field named **label - cust1**.

Source Side

Outgoing sync

```
replica.customFields."label - cust1" = issue.customFields."label - cust1"
```

Destination Side

Incoming sync

- Set the received label to the local label custom field and if it doesn't find one, it sets an empty array so you don't get a null pointer exception.

Note: This method overrides all the existing labels in the custom field.

```
issue.customFields."label - cust1".value = replica.customFields."label - cust1"?.value ?: []
```

- Add the received label into the local label custom field

```
issue.customFields."Labels".value += replica.customFields."label - cust1"?.value
```

How to Set a Default Value in a Label Custom Field?

To set a default value in a label custom field use the [nodeHelper](#).`getLabel` method.

```
issue.customFields."Epic/Theme".value = replica.customFields."Tags"?.value ?: [
    nodeHelper.getLabel("")
]
```

Product

ON THIS PAGE

[About Us](#)

[Release History](#)

[Source Side](#)

[Glossary](#)

[Destination Side](#)

[API Reference](#)

[How to Set a Default Value in a Label Custom Field?](#)

[Pricing and Licensing](#)

Resources

[Subscribe for a weekly Exalate hack](#)

[Academy](#)

[Blog](#)

[YouTube Channel](#)

[Ebooks](#)

Still need help?

[Join our Community](#)

[Visit our Service Desk](#)

[Find a Partner](#)