

# How to Sync Custom Fields with Options in Jira On-premise

Last Modified on 02/11/2026 9:29 am EST

This article describes how to synchronize custom fields that have options as a value type.

Jira has different custom field types with options:

- Select list (Single choice)
- Radio buttons (list of radio buttons)
- Select list (Multiple choices)
- Checkboxes (multiple choices)

Below you can find some examples on how to handle the most common cases related to the custom fields with option values.

## Select List (single choice)

Custom fields with types **Select List(single choice)** and **Radio buttons(single choice)** have values of type [Option](#).

You can apply the received option in different ways on your side:

- set an option manually directly in the Sync Rules

```
issue.customFields."Hobby".value = "Running"
```

- add the received value from the remote custom field into the local custom field

If the received custom field does not have any values yet, you can still set a custom field with a default value as empty

```
issue.customFields."Hobby".value = replica.customFields."Interest"??.value
```

- Set a default option in case there's no value received from the remote side

```
issue.customFields."Hobby".value = replica.customFields."Interest"??.value ?: "Hobby"
```

- Map options between instances

```
def hobbyMap = ["Futbol": "Soccer", "Beisbol": "Baseball"] // ["remote options" : "local option"]
def remoteHobby = replica.customFields."Hobby"??.value??.value
issue.customFields."Hobby".value = hobbyMap[remoteHobby] ?: remoteHobby
```

## Select List (multiple choices)

Custom fields with types **Select List(multiple choices)** and **Checkboxes(multiple choices)** have values of type [list of Options](#).

Below you can find some examples of how to handle custom field options in ***multi-value custom fields***.

- Set an option value manually into the local custom field

```
issue.customFields."Multi Select Custom Field name".value =  
(issue.customFields."Multi Select Custom Field name".value ?: []) +  
nodeHelper.getOption(issue, "Multi Select Custom Field name", "MY STATIC OPTION")
```

- add the value from the remote custom field **Departments** into the local custom field **Sub-divisions**

Leave an empty field in case there's no option, received from the remote side.

```
issue.customFields."Sub-divisions".value = replica.customFields."Departments"??.value
```

- Set a default option in case there's no value received from the remote side

You need to ensure that the value is an array of options.

```
issue.customFields."Hobby".value = replica.customFields."Interest"??.value ?: ["Running"]
```

- Map options in a select list

```
def hobbyMap = ["Football": "Sports", "Baseball": "Basketball"]  
def remoteHobbies = replica.customFields."Hobby"??.value?.value  
issue.customFields."Hobby".value = remoteHobbies.collect{hobbyMap[it] ?: it}
```

[Product](#)

[About Us](#) 

[ON THIS PAGE](#)

[Glossary](#) 

[Select List \(single choice\)](#)

[API Reference](#) 

[Select List \(multiple choices\)](#)

[Security](#) 

[Pricing and Licensing](#) 

[Resources](#)

[Subscribe for a weekly Exalate hack](#) 

[Academy](#) 

[Blog](#) 

[YouTube Channel](#) 

[Ebooks](#) 

[Still need help?](#)

[Join our Community](#) 

[Visit our Service Desk](#) 

[Find a Partner](#) 